

Amendments to the Claims:

Please amend claims 1, 18, 19, and 23. This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) An apparatus for aggregating device communications, the apparatus comprising:
a plurality of local ports including at least one wired local port and at least one wireless local port, ~~the local ports each~~ at least one wired local port and at least one wireless local port being configured to establish bi-directional data communications with at least one respective local device terminating a communications path, and at least two of the local ports using different communication protocols;
a remote access port, the remote access port configured to establish bi-directional, wireless, data communications with a service provider; and
a processing system for converting data signals between a form adapted to one of the plurality of local ports and a form adapted to the remote access port.
2. (Original) The apparatus of claim 1, the processing system further comprising a port processing unit that converts data signals between a form adapted to more than one of the plurality of local ports into a form adapted to a multiple access air interface of the remote access port.
3. (Original) The apparatus of claim 1, the processing system further comprising a shared signal processing unit that converts data signals between a form adapted to

more than one of the plurality of local ports into a form adapted to a single channel of the remote access port.

4. (Previously Presented) The apparatus of claim 1, wherein the apparatus is shaped and sized to be worn by a person.
5. (Original) The apparatus of claim 1 wherein the plurality of local ports include at least one of a Bluetooth port, a HomeRF port, an IrDA port, a wireless Ethernet port, a wired serial port, a wired parallel port, or a wireless local area network port.
6. (Original) The apparatus of claim 1 wherein the remote access port includes a wireless port.
7. (Original) The apparatus of claim 6 wherein the wireless port includes at least one of a CDMA port, a TDM port, a GSM port, a PCS port, or a third generation cellular telephony port.
8. (Original) The apparatus of claim 1, the service provider connected in a communicating relationship with the remote access port through an air interface establishing bi-directional wireless data communications with the remote access port, and the service provider including an Internet connection, whereby a local device connected in a communicating relationship with one of the plurality of local ports may communicate through the Internet.
9. (Original) The apparatus of claim 1 further comprising a local device connecting in a communicating relationship with one of the plurality of local ports, the local

device including at least one of a personal digital assistant, a notebook computer, a laptop computer, a cellular phone, a palm computer, or a wearable computer.

10. (Original) The apparatus of claim 9, the wearable computer including at least one of a wearable eyeglass computer or a wearable audio computer.
11. (Original) The apparatus of claim 1, the remote access port including a plurality of data channels, the bi-directional wireless data communications being distributed among two or more of the plurality of data channels.
12. (Previously Presented) The apparatus of claim 1 wherein the apparatus is at least one of a portable accessory, a modular add-on device, or a base station accessory.
13. (Original) The apparatus of claim 1, the processing system further comprising one or more processors that convert traffic between data for more than one of the plurality of local ports and data for a logical channel of the remote access port.
14. (Original) The apparatus of claim 1, the processing system further comprising one or more processors that convert traffic between data for more than one of the plurality of local ports and data for a plurality of logical channels of the remote access ports.
15. (Original) The apparatus of claim 1 further comprising a services unit that provides network services to the plurality of local ports.
16. (Original) The apparatus of claim 15, the network services including at least one of device connectivity, error detection and correction, load balancing, caching,

traffic management, congestion control, file sharing, printer sharing, and distributed computing.

17. (Original) The apparatus of claim 1 wherein the plurality of local ports comprise a terminal port cluster, the terminal port cluster including a plurality of connectors, each connector adapted to removably receive a modular device port, the modular device port adapted to a single communications technique.

18. (Currently Amended) A system for aggregating device communications, the apparatus comprising:

- a plurality of local communications means for maintaining communications with one or more local devices, the plurality of local communications means including at least one wired local communications means and at least one wireless local communications means configured to establish bi-directional data communications with the one or more local devices terminating a communications path, at least two of the local communications means using different communications protocols;
- a remote communications means for maintaining wireless communications with a service provider; and
- a converting means for converting data signals between a form adapted to the plurality of local communications means and the remote communications means.

19. (Currently Amended) A method for aggregating device communications, the method comprising:
receiving local data from a plurality of local devices terminating a communications path via at least one wired local communications port and at least one wireless local communications port, at least two of the local communications ports using different communications protocols;
converting the local data into converted local data, the converted local data having a form suitable for transmission over a wireless communication link;
transmitting the converted local data over the wireless communication link;
receiving network data from a service provider over the wireless communication link;
converting the network data into converted network data, the converted network data having a form suitable for transmission to one or more of the plurality of local devices; and
transmitting the converted network data to one or more of the plurality of local devices via at least one of the wired or wireless local communications ports.
20. (Original) The method of claim 19 wherein converting the local data includes multiplexing the local data into a plurality of data streams corresponding to more than one channel of a multiple access wireless interface.
21. (Original) The method of claim 19 wherein converting the local data includes sequentially converting the local data from selected ones of the plurality of local devices.
22. (Original) The method of claim 19 wherein converting the local data includes prioritizing the plurality of local devices and converting data from a selected one

Applicant : Rahul R. Vaid
Serial No. : 09/746,484
Filed : December 21, 2000
Page : 8 of 13

Attorney's Docket No.: 14892-011001

of the plurality of local devices according to a priority of the selected one of the plurality of local devices.

23. (Currently Amended) An apparatus for aggregating device communications, the apparatus comprising:
- a plurality of local ports including at least one wired local port and at least one wireless local port, the local ports each configured to establish bi-directional data communications with at least one respective local device terminating a communications path, and at least two of the local ports using different communication protocols;
 - a remote access port, the remote access port configured to establish bi-directional, wireless, data communications with a service provider;
 - a processing system for converting data signals between a form adapted to one of the plurality of local ports and a form adapted to the remote access port; and
 - a services unit that provides network services to one or more local devices connected to the plurality of local ports.
24. (Previously Presented) The apparatus of claim 1, wherein said processing system is configured to facilitate a communications path between multiple local ports.
25. (Previously Presented) The apparatus of claim 1, wherein the at least two local ports further use different data rates and different data formats.
26. (Previously Presented) The apparatus of claim 19, further comprising facilitating a communications path between multiple local ports.
27. (Previously Presented) The apparatus of claim 19, wherein receiving local data is performed at different data rates and different data formats.

28. (Previously Presented) The apparatus of claim 23, wherein said processing system is configured to facilitate a communications path between multiple local ports.
29. (Previously Presented) The apparatus of claim 23, wherein the at least two local ports further use different data rates and different data formats.